

Starter Batteries

BACK-UP POWER



intAct BackUp-Power

Sealed maintenance-free calcium battery (Ca/Ca) | electrolyte held in Absorbent Glass Mat separators (AGM) | wet charged



intAct
BATTERY - POWER

SUPPORT FOR THE STARTER BATTERY

Supplies consumers in certain types of vehicles and keeps them charged during the start-up, thus protecting the electronics. Our recommendation as a reliable alternative to the original installed back-up battery.

- » Increased cold start performance.
- » Longer life expectancy. Three times more cycle resistant than conventional starter batteries.
- » Wet charged. Ready to use.
- » Sealed valve-regulated battery (VRLA) with gas recombination.
- » Sealed maintenance-free and leak-proof.
- » Electrolyte held in glass fibre mat.
- » Lead-calcium alloy grid plates.



Artnum. BU09

Japan-Code keine

Volt 12V

Capacity 9 AH (c20)

CCR - 18° C (EN) 120 A (EN)


Electrolyte diluted sulphuric acid

Electrolyte density 1,28 +/- 0,01 Kg/l (25° C)

Size (LxWxH) 150 x 87 x 105 mm

Weight 3,3 kg

Pos. of Terminal 1



Technology Sealed maintenance-free calcium battery (Ca/Ca)
| electrolyte held in Absorbent Glass Mat
separators (AGM) | wet charged

Terminal screw terminal

Base plate -

