Starter Batteries



intAct Start-Power NG

Maintenance-free calcium battery (Ca/Ca) | wet charged











ONE THAT FITS ALL

Fully meets the requirements of all vehicles. Both for older vehicles as well as for newer models with charging voltage up to 14.8 volts. For passenger cars, also from Asia and super-shakeproof for trucks. Our recommendation for a solid battery when cost is a major consideration.


- » Approved for charging voltage up to 14.8 volts.
- » Very powerful, maintenance-free and extremely reliable.
- » Double lid for increased leak protection and vapour condensation (gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).
- » 2 versions: For cars (including Asia models) and Super-Heavy-Duty (SHD) for trucks.
- » SHD version with glass mat separators vibration-resistant V3. For complexly equipped, heavy commercial vehicles even under the most difficult conditions.


Datasheet



Artnum.	54324GUG
Japan-Code	keine
Volt	12V
Capacity	43 AH (c20)
CCR -18°C (EN)	440 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	210 x 175 x 175 mm
Weight	11,4 kg
Pos. of Terminal	0









As of 23.11.2022