



SBL33-12i (12V33Ah)



Applications

- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Emergency light
- Railway signal
- Alarm and security system
- Communication power supply
- DC power supply

Certificates

Conform to
IEC60896-21&22


Specifications

Nominal Voltage	12V	Nominal Oper. Temp. R.	20±3°C
Nominal Capacity	33.0Ah (C ₁₀ , 10.8V)	Operating Temp. Range	Discharge: -20~50°C Charge: -10~50°C Storage: -20~50°C
Approx. Weight	9.7kg	Standby Use	No limit on Initial Charging Current. Voltage 2.295 V/cell at 20° C. Temperature Coefficient 3mV/cell/°C.
Terminal	M6	Capacity affected by Temp.	40°C 103% 25°C 100% 0°C 86%
Container Material	ABS UL94 HB	Self Discharge	SSB batteries may be stored for up to 6 months at 20°C and then a freshening charge is required. For higher temperatures the time interval will be shorter.
Rated Capacity (20°C)	35.0Ah/1.75A,20hr, 10.8V 33.0Ah/3.30A,10hr, 10.8V 31.36Ah/3.92A,8hr, 10.5V 27.90Ah/5.58A,5hr, 10.5V 24.75Ah/8.25A,3hr,10.5V 22.3Ah/22.3A,1hr, 9.6V	Life Expectancy	10-12 years according to EUROBAT
Max. Discharge Current	330A (5s)		
Internal Resistance / Impedance (1kHz)	Approx. 12mΩ		

Dimensions

■ M6 Terminal

Unit: mm | Dimensions: 195 Length X 130 Width X 155 Height (168 Height incl. Terminal)




Constant Current Discharge (Amperes) at 20°C

F.V/Time	10min	15min	30min	1h	1.5h	2h	3h	5h	6h	8h	10h	20h
1.60V/cell	69.3	57.1	32.6	22.3	16.6	12.8	9.08	6.3	5.38	4.15	3.36	1.81
1.65V/cell	65	54.1	31.3	21.9	16.3	12.6	8.97	6.25	5.23	4.07	3.35	1.79
1.70V/cell	60	51.4	30.4	21.2	15.8	12.1	8.45	6.15	5.09	3.99	3.32	1.78
1.75V/cell	56.1	47.8	29.4	20.3	15.1	11.65	8.25	5.58	4.95	3.92	3.31	1.76
1.80V/cell	51.4	44.8	28.8	19.8	14.8	11.42	8.18	5.5	4.81	3.85	3.30	1.75


Constant Power Discharge (Watts/cell) at 20°C

F.V/Time	10min	15min	30min	45min	1h	1.5h	2h	3h	5h	8h
1.60V/cell	122	100	65.3	45.5	40.9	30.4	23.3	17.4	12.2	6.48
1.65V/cell	116	98.6	61.7	44.2	40.5	30.2	23.1	17.3	11.9	6.32
1.70V/cell	110	95.7	61.7	43.5	39.9	29.6	22.6	16.8	11.5	6.1
1.75V/cell	104	92	58	42.5	39.1	28.9	21.8	16	11.3	6
1.80V/cell	97.7	89	56	41.5	38.3	28.1	21	15.2	11	5.84


Discharge Characteristics



Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life

