

Powered by

WAMTECHNIK

Rechargeable Li-ion battery pack – 1689.01.001.4

Configuration: 1S4P




Dimensions:

Length: 74 ±1mm

Width: 21,5 ±1mm

Height: 69 ±1mm



Data for pack

Nominal Voltage		3.65V	
Rated Capacity		10.68Ah	
Used cell in Pack		4pcs	INR18650-29E
Internal resistance pack		67mΩ	±10%
Max charge voltage		4.2V	25°C
Charge current	standard	4.5A	25°C
	rapid	-	-
Discharge	standard	2A	25°C
	max. cont.	4.5A	25°C
	max. Peak	8A	25°C t<5s
Short Circuit current		38A	t<3ms
Cable length		150mm	±5mm
Connector		Molex	MiniFit 39-01-2020
Weight		195g	±10g
Connector		Molex	MiniFit 39-01-2020
Watt-hour rating		39Wh	
Charge temperature		standard	0°C - 45°C
		rapid	10°C - 40°C
Discharge temperature		standard	-20°C - 60°C
Storage temperature		1 year	0~23°C
Note 1: Self discharge <1% / month			
Note 2: Delivery SOC aprox. 30%			

Limitations by Safety Unit (SU)

Over Voltage (per cell)	cut off	4.325V	
	release	4.075V	±0.025
Under Voltage (per cell)	cut off	2.5V	
	release	2.9V	±0.05
Current Limit 1 by SU		8A	t ~10ms
Current Limit 2 by SU		10.2	t ~18ms
Power Consumption	active		